

W11 THREE-ROLLER MECHANICAL METAL SHEET
ROLLING MACHINE

ITEM	UNIT	W11-6X1500	W11-6X2000	W11-6X2500	W11-6X3200	W
Max Rolling Thickness	mm	6	6	6	6	
Max Rolling Width	mm	1500	2000	2500	3200	
Plate Yield Limit	Mpa	265	265	265	265	
Rolling Speed	m/min	7.16	7.16	7.16	6.46	
Minimum Coil Loaded Diameter	mm	380	380	500	500	
Upper Shaft Diameter	mm	180	180	190	240	
Under Shaft Diameter	mm	160	160	170	200	
Two Lower Shaft Center Distance	mm	210	210	260	310	

W11 THREE-ROLLER MECHANICAL METAL SHEET ROLLING MACHINE

ITEM	UNIT	W11-6X1500	W11-6X2000	W11-6X2500	W11-6X3200	W
Max Rolling Thickness	mm	6	6	6	6	
Max Rolling Width	mm	1500	2000	2500	3200	
Plate Yield Limit	Mpa	265	265	265	265	
Rolling Speed	m/min	7.16	7.16	7.16	6.46	
Minimum Coil Loaded Diameter	mm	380	380	500	500	
Upper Shaft Diameter	mm	180	180	190	240	
Under Shaft Diameter	mm	160	160	170	200	
Two Lower Shaft Center Distance	mm	210	210	260	310	

W11 THREE-ROLLER MECHANICAL METAL SHEET ROLLING MACHINE

ITEM	UNIT	W11-6X1500	W11-6X2000	W11-6X2500	W11-6X3200	W
Max Rolling Thickness	mm	6	6	6	6	
Max Rolling Width	mm	1500	2000	2500	3200	
Plate Yield Limit	Mpa	265	265	265	265	
Rolling Speed	m/min	7.16	7.16	7.16	6.46	
Minimum Coil Loaded Diameter	mm	380	380	500	500	
Upper Shaft Diameter	mm	180	180	190	240	
Under Shaft Diameter	mm	160	160	170	200	
Two Lower Shaft Center Distance	mm	210	210	260	310	

W11 THREE-ROLLER MECHANICAL METAL SHEET
ROLLING MACHINE

ITEM	UNIT	W11-6X1500	W11-6X2000	W11-6X2500	W11-6X3200	W
Max Rolling Thickness	mm	6	6	6	6	
Max Rolling Width	mm	1500	2000	2500	3200	
Plate Yield Limit	Mpa	265	265	265	265	
Rolling Speed	m/ min	7.16	7.16	7.16	6.46	
Minimum Coil Loaded Diameter	mm	380	380	500	500	
Upper Shaft Diameter	mm	180	180	190	240	
Under Shaft Diameter	mm	160	160	170	200	
Two Lower Shaft Center Distance	mm	210	210	260	310	

W11 THREE-ROLLER MECHANICAL METAL SHEET ROLLING MACHINE

ITEM	UNIT	W11-6X1500	W11-6X2000	W11-6X2500	W11-6X3200	W11-6X4000
Max Rolling Thickness	mm	6	6	6	6	6
Max Rolling Width	mm	1500	2000	2500	3200	4000
Plate Yield Limit	Mpa	265	265	265	265	265
Rolling Speed	m/min	7.16	7.16	7.16	6.46	5.76
Minimum Coil Loaded Diameter	mm	380	380	500	500	630
Upper Shaft Diameter	mm	180	180	190	240	280
Under Shaft Diameter	mm	160	160	170	200	240
Two Lower Shaft Center Distance	mm	210	210	260	310	360